

Skyfens Supro Loft Triple Termo

Skyfens Supro Loft Triple Termo roof hatches offer excellent thermal insulation thanks to a triple glazing package with a warm frame (Uw 1,1 W/m^2K). Ideal for large roof openings, they provide a balance between cost and energy efficiency.

SKYFENS SUPRO LOFT TRIPLE TERMO















Energy efficiency	

- 3-glazed package with TGI Spacer warm frame
- simple classic profile
- parameter Uw=1,1 W/m²K

Material

- Lead-free PVC
- steel reinforcements

Opening

- manual to the side
- sizes 6/X and 7/X with gas spring actuators
- can be opened to the right or to the left side of the roof

Handle

• two passive ventilation positions

Technical data:

Coefficient Uw	Coefficient Ug	Sound insulation	Air permeability	Watertightness class	Wind load resistance
1,1 W/m ² K	0,5 W/m ² K	32 dB	class 4	class E1200	class C4

- SUPRO Roof Hatches with a triple-glazed package and a warm TGI
 Spacer frame effectively reduce the heat transfer coefficient (Uw)
 to 1,1 W/m²K. They are ideal for both heated and unheated spaces
 due to their excellent thermal insulation properties.
- Innovative Hinge. Enhanced safety and functionality thanks to the new hinge, which not only increases durability but also allows for smooth adjustment of the window sash, ensuring a perfect fit.
- Additional Dimension Options We have introduced new, large sizes for roof windows: 6/11 and 7/11, which meet the needs of projects requiring larger installation solutions and provide additional light space.
- Accessibility and Ergonomics The roof windows can be opened to the right or left, facilitating roof access. Side opening with a lock ensures that the sash remains open at a 90-degree angle.
- Innovative Opening Mechanisms For sizes 5/7 and 5/9, a casement mechanism is used, which facilitates manual opening and closing operations. In larger sizes 6/9, 6/11, 7/9, and 7/11, double gas struts with a damping function are installed, ensuring smoothness and safety in use.
- Standard dimensions of the hatches:

5/7*	5/9*	6/9**	6/11**	7/9**	7/11**	
550x780	550x980	660x980	660x1180	780x980	780x1180	

^{*} dimensions of egress hatches with hinge installed

- Optimal Protection Against External Conditions thanks to four seals resistant to low temperatures, which provide maximum tightness of the roof hatch.
- Aesthetics and Easy Maintenance The roof window has a classic design that fits well with various interior styles and requires minimal maintenance, limited to occasional washing.
- Passive Ventilation The handle allows the roof hatch to be cracked open in two positions, enabling effective and adjustable ventilation.
- Installation on Various Roof Slopes and Coverings The roof window can be installed on roofs with a slope of 15 to 70 degrees and on any type of roof covering, offering wide compatibility and flexibility in adapting to various roof constructions.



^{**} dimensions of egress hatches with fitted gas spring assisted opening