## **Roof windows**

# **SKYLIGHT PREMIUM**

**Skylight Premium** roof windows are characterised by their original, rounded profile geometry. Thermal transmittance of the window Uw=1,4W/m<sup>2</sup>K.



## **SKYLIGHT PREMIUM**













| Energy efficiency | <ul> <li>2-pane package</li> <li>original, rounded profile</li> <li>Uw=1,4 W/m²K</li> </ul> |  |  |  |  |  |
|-------------------|---|--|--|--|--|--|
| Material          | <ul><li>lead-free PVC</li><li>steel reinforcement</li></ul>                                 |  |  |  |  |  |
| Axis of rotation  | • elevated (3/4 window)   |  |  |  |  |  |
| Opening           | • manual  |  |  |  |  |  |
| Handle            | <ul><li>mounted on the bottom</li><li>1 position of passive ventilation</li></ul>           |  |  |  |  |  |

#### Technical data:

| Window                 | Glazing                | Acoustic   | Air          | Water           | Wind load  |  |
|------------------------|------------------------|------------|--------------|-----------------|------------|--|
| U-value                | U-value                | insulation | permeability | tightness class | resistance |  |
| 1,4 W/m <sup>2</sup> K | 1,1 W/m <sup>2</sup> K | 30 dB      | class No. 4  | class No. E1200 |            |  |

- The unique rounded profile, in combination with the 2-pane package, guarantees the sustainable balance of thermal energy acquisition and loss. Uw = 1,4 W/m<sup>2</sup>K.
- Longer lifespan. Aesthetic PVC, resistant to ageing, not sensitive to moisture and temperature changes, ideal for every room at your home.
- 3/4 elevated axis of rotation improves visibility from the window and easy access.
- **Design**. This window with the original rounded profile will satisfy all the designing requirements.
- **Original patented system of fittings** guarantees full sash stability both in the half-open function, open function and rotational function with the maximum safety.
- A package of four seals resistant to low temperatures ensures the perfect tightness of Skylight roof window.
- Possible installation on roofs with an angle of inclination of 15 to 70 degrees.

- The external roof window flashing protects fittings against atmospheric conditions and improves the sealing of the casingsash connection.
- **Shock absorption fitting** does not need any adjustment. No special maintenance treatment required. It needs only washing.
- A comfortable position for washing the external side of the window sash rotation by 120.



### Standard window dimensions:

| 5/7     | 5/9     | 5/11     | 6/9     | 6/11     | 6/14     | 7/9     | 7/11     | 7/14     | 7/16     | 9/11     | 9/14     | 11/11     | 11/14     |
|---------|---------|----------|---------|----------|----------|---------|----------|----------|----------|----------|----------|-----------|-----------|
| 550x780 | 550x980 | 550x1180 | 660x980 | 660x1180 | 660x1400 | 780x980 | 780x1180 | 780x1400 | 780x1600 | 940x1180 | 940x1400 | 1140x1180 | 1140x1400 |